



GREEN LIFE
WINDOWS + DOORS



GREEN LIFE

WINDOWS + DOORS



MANUFACTURER LIMITED WARRANTY

GL CLASSIC SERIES AWNING WINDOWS

Experience the perfect blend of elegance and durability with our premium awning windows. Designed to withstand the harshest environments, they offer unmatched protection while enhancing your space's beauty. Enjoy superior safety, seamless functionality, and timeless style—all in one sleek, durable design.



Technical Characteristics | GL Classic Series Awning Windows

Serviceability	±2000pa
Ultimate Pressure	±3000Pa
Design Water Resistance	300pa
Sound Insulation	-37db
Uw Range	3.8 ~ 4.5
SHGC Range	0.18 ~ 0.51
Maximum height	1800mm
Maximum width	1800mm
Maximum adaptive weight	100kg
Available glazing	6 ~ 28mm
Frame Dimensions (depth & width)	76mm * 35mm sill
Extrusion profiles	6063-T5 with 1.4mm thickness
Powder Coating	Dulux / Interpon Powder Coatings
Fixing Method	Subsill & head / Fin fix / Timber reveal

GL COMMERCIAL SERIES HINGED DOORS

Where superior strength meets stunning design. Tailored for commercial spaces and luxury homes, these top-tier doors boast 50mm-thick substantial stiles that eclipse the market's typical 44mm standard. Transform your entrance with unparalleled durability and a bold statement of quality.



Technical Characteristics | GL Commercial Series Hinged Doors

Serviceability	±2200pa
Ultimate Pressure	±3300pa
Design Water Resistance	300pa
Sound Insulation	-36db
Uw Range	3.7 ~ 4.3
SHGC Range	0.28 ~ 0.52
Maximum height	2700mm
Maximum width	1000mm
Maximum adaptive weight	90kg
Available glazing	6mm ~ 30mm
Frame Dimensions (depth & width)	100mm * 50mm sill
Extrusion profiles	6063-T5 with 2.2mm thickness
Powder Coating	Dulux / Interpon Powder Coatings
Fixing Method	Subsill & head / Fin fix / Timber reveal

GL COMMERCIAL SERIES SLIDING DOORS

Where commercial grade excellence meets everyday elegance. Engineered for Aussie homes and offices, these doors feature a stainless-steel track, heavy-duty nylon runners, premium Doric hardware, and a sturdy stainless-steel flyscreen. Enjoy smooth, whisper-quiet operation, uncompromising security with a touch of sophistication—perfect for blending urban sophistication with coastal breezes.



Technical Characteristics | GL Commercial Series Sliding Doors

Serviceability	±2200pa
Ultimate Pressure	±3300pa
Design Water Resistance	300pa
Sound Insulation	-39db
Uw Range	3.2 ~ 3.9
SHGC Range	0.31 ~ 0.59
Maximum height	3000mm
Maximum width	1750mm
Maximum adaptive weight	250kg
Available glazing	6mm ~ 26mm
Frame Dimensions (depth & width)	100mm * 50mm & 150mm * 50mm sill
Extrusion profiles	6063-T5 with 2.5mm thickness
Powder Coating	Dulux / Interpon Powder Coatings
Fixing Method	Subsill & head / Fin fix / Timber reveal

GL SIGNATURE SERIES BI-FOLD DOORS

Where premium thermally broken technology meets exceptional strength and outstanding thermal efficiency. Featuring an 80mm commercial-grade extruded frame with a flawless high-quality powder coat finish, these doors deliver unparalleled durability and striking sophistication. Perfect for commercial spaces and upscale homes, they redefine elegance while seamlessly blending indoor comfort with outdoor freshness.



Hardware

KSBG Bi-fold Door Hardware

- > Origin Country: Germany
- > Colour: Black, Silver



Handle



Hinge



Upper load-bearing Pulley

Powder Coating Finishing

Standard Colour

Standard powder coating options (Black, Monument, White).
Standard 10-year warranty, upgradeable to higher weather resistance.



Black Satin Interpon
GN150A



Monument Matt Interpon
YL264A



Pearl White Gloss Interpon
YA075A

Customised Colour

Powder coating customised colour options.



Dulux

Interpon.
POWDER COATINGS



interpon

Dulux Powder Coatings is the largest powder supplier in Australia & NZ and offers a wide range of stock & custom colours, by selecting a Dulux Accredited Powder Coater you can guarantee that you're getting the best for your project.

Interpon Powder Coatings, part of the AkzoNobel group, is the largest global manufacturer of powder coatings and a world leader in powder coatings technology. Interpon powder coatings are available in a wide variety of colors, finishes and performance properties tailored to the customer's needs.

Project Overview



Williamstown North VIC 3016



Kew VIC 3101



Strathmore VIC 3041



Eaglemont VIC 3084



Wheeler's Hill VIC 3150



MELBOURNE

Unit 5/409 Princes Hwy, Noble Park VIC 3174
+61 3 9115 1833
Hotline: 1300 008 886 ext.1
sales@greenlifewindows.com.au

BRISBANE

Unit 3/58 Compton Road, Wodridge QLD 4114
+61 490 083 068
Hotline: 1300 008 886 ext.4
brisbane@greenlifewindows.com.au

SYDNEY

Unit 2/95 St Hiliers Road, Auburn NSW 2144
+61 2 9062 5771
Hotline: 1300 008 886 ext.2
sydney@greenlifewindows.com.au

INSTALLATION SERVICE NATION WIDE

10 Americain Way, Dandenong South VIC 3175
Jimmy Liu
+61 411 453 303
Install@greenlifewindows.com.au

ADELAIDE

61 South Road, Thebarton SA 5031
+61 8 8234 7367
Hotline: 1300 008 886 ext.3
adelaide@greendows.com.au

CHINA

No.178 Zhaoshang Avenue, China Merchants
Zhangzhou Development Zone, Zhangzhou City
, Fujian Province, P.R.China
+86 181 5076 5652
admin@bo-lang.cn

For more information
www.greenlifewindows.com.au